

# TCH-SWD CARTRIDGE FILTER HOUSING





MEY's TCH-SW Seriesis a comprehensive range of cartridge filter housings. The heavy duty swing bolt top closure with Davit arm hand wheel assist open to allow quick filter cartridge change out. The housing hold filter cartridges 12, 22 rounds, in either 30-inch, or 40-inch lengths, accepts DOE and 222 filter cartridges in common.

#### **Typical Application:**

- Water treatment
- Municipal Water Treatment
- Industrial Water Treatment
- Pulp and Paper
- Pharmaceutical
- Lubricants, Metalworking Fluids
- Solvents
- Food and Beverage
- Chemical Processing
- Paints, Inks, Resins and Coatings
- Electronics
- Petrochemicals

#### **Filter Specifications**

#### Cartridge Size

30", 40"

#### Number of Cartridge

12, 22 Rounds

#### Cartridge Support

DOE, 222

#### **Housing Material**

SS304, SS316L, CARBON STEEL

#### Inlet & Outlet


DIN / ANSI / BSP / NPT


#### Max. Operating Temperature

150 ℃

#### Max. Operating Pressure

10Bar (150PSI)





Qty of	Ф Н mm (inch)				
Cartridge					
12 Rounds	431.6 (17.0)				
22 Rounds	533.5 (17.0)				

All Dimensions are for reference only

#### **12 Round Housing**

Length	Flow rate	Connection	Dimensions,mm					
	Gpm(m³/hr)	Inlet/Outlet	А	В	С	D	E	F
30"	180(40.9)	3"RF FI	356	325	500	1288	1718	479.6
40"	240(54.5)	3"RF FI	356	325	500	1542	1972	479.6

### **21** Round Housing

Length	Flow rate	Connection	Dimensions,mm					
	Gpm(m³/hr)	Inlet/Outlet	A	В	С	D	E	F
30"	315(71.6)	4"RF FI	457	384.2	616.6	1384	1846	548.8
40"	420(95.5)	4"RF FI	457	384.2	616.6	1638	2100	548.8

Note:1,Above Flow rate is for guide line only. 2,Flow rate is based on 5gpm/TIE 25 micron string wound. Cartridge and clean water(viscosity cp=1) at 2PSID All dimensions are for reference.

## **Order Information**

тсн	-03	-02	SS304	1.5T	SWD	GB
Model	Qty of Cartridges	Cartridge Length	Material	INLET/OUTLET SIZE	TOP CLOSURE	Surface Finish
тсн	12=12 rounds 22=22 rounds	30=30" 40=40"	SS304 SS316L	3F=3"RF Flange 3T=3" NPT 3VC=3" Victaulic 4F=4"RF Flange 4T=4" NPT 4VC=4" Victaulic	SW=Swing Bolt Davit	GB=Glass bead PC=Poly coat EP=Electro-polishing



Mey Membrane Technology Co.,Ltd Add.:Fuyang district,Hangzhou

Tel.:0571-63465770